

# SmartCompression™ EMT

with the Only Pre-installed Raintight Coupling




SmartCompression EMT has the only pre-installed raintight coupling, enabling faster installation. It can be coupled 3x faster than standard couplings, and its smooth ID coating allows for faster wire pulling. SmartCompression EMT is produced from FasTrak® Plus EMT and is available in trade sizes 2-4 and lengths of 10' and 20'.

## Listing

SmartCompression EMT is listed to safety standards UL-797 and UL-514B for fittings.

SmartCompression EMT is manufactured in accordance with ANSI® C80.3.



## Locations

SmartCompression EMT is raintight and concrete tight. It is ideal for use outdoors, in wet locations, underground, in concrete and in other areas that may be exposed to weather.

## Coatings

SmartCompression EMT is galvanized with a clear top coat, and the compression fitting is zinc-electroplated to inhibit corrosion.

## SMARTCOMPRESSION EMT WEIGHTS AND DIMENSIONS

TRADE SIZE	OD	ID*	WALL THICKNESS	MINIMUM WEIGHT EMT	COUPLING WEIGHT	MASTER BUNDLE QUANTITY	MASTER BUNDLE WEIGHT
				lbs./ft.	lbs.	ft.	lbs.
2	2.197	2.067	0.065	1.400	0.480	500	723
2½	2.875	2.731	0.072	2.050	1.060	350	757
3	3.500	3.356	0.072	2.500	1.300	300	832
3½	4.000	3.834	0.083	3.250	1.540	250	891
4	4.500	4.334	0.083	3.700	1.790	250	1010


Note: SmartCompression EMT is listed to safety standards UL-797 and UL-514B and is manufactured in accordance with ANSI C80.3.  
\*For information only; not a standards requirement.

All electrical systems must be installed per local code and AHJ requirements.

## SUBMITTAL INFORMATION

PROJECT: \_\_\_\_\_ CONTRACTOR: \_\_\_\_\_ DATE: \_\_\_\_\_  
ENGINEER: \_\_\_\_\_ SPECIFICATION REFERENCE: \_\_\_\_\_ SYSTEM TYPE: \_\_\_\_\_  
LOCATIONS: \_\_\_\_\_ COMMENTS: \_\_\_\_\_

WEL-090116

 700 South Dock Street  
Sharon, PA 16146  
P 800.257.8182  
F 724.346.7260

info@wheatland.com  
wheatland.com  
Follow us on Twitter:  
@WheatlandTube

 **Wheatland** Tube  
A DIVISION OF ZEKELMAN INDUSTRIES