

ROUNDS

OD	GAUGE & NOMINAL WALL THICKNESS															
	20 0.035	19 0.042	18 0.049	17 0.058	16 0.065	15 0.072	14 0.083	13 0.095	12 0.109	11 0.120	10 0.134	9 0.148	8 0.165	7 0.180	6 0.203	5 0.220
0.706	0.2511	0.2981	0.3441	0.4018	0.4454	—	—	—	—	—	—	—	—	—	—	—
0.750	0.2675	0.3179	0.3672	0.4291	0.4760	—	—	—	—	—	—	—	—	—	—	—
0.815	0.2918	0.3471	0.4012	0.4694	0.5211	0.5719	0.6495	—	—	—	—	—	—	—	—	—
0.875	0.3143	0.3740	0.4327	0.5066	0.5628	0.6181	0.7027	—	—	—	—	—	—	—	—	—
0.922	0.3319	0.3951	0.4573	0.5357	0.5955	0.6542	0.7444	—	—	—	—	—	—	—	—	—
0.995	0.3592	0.4279	0.4955	0.5810	0.6462	0.7104	0.8092	0.9140	1.0324	—	—	—	—	—	—	—
1.000	0.3611	0.4301	0.4981	0.5841	0.6497	0.7143	0.8136	0.9191	1.0382	—	—	—	—	—	—	—
1.029	0.3719	0.4431	0.5133	0.6020	0.6698	0.7366	0.8394	0.9485	1.0720	1.1661	—	—	—	—	—	—
1.050	0.3798	0.4526	0.5243	0.6151	0.6844	0.7527	0.8580	0.9699	1.0965	1.1930	—	—	—	—	—	—
1.125	0.4078	0.4862	0.5636	0.6616	0.7365	0.8105	0.9245	1.0460	1.1839	1.2892	—	—	—	—	—	—
1.163	0.4220	0.5033	0.5835	0.6851	0.7629	0.8397	0.9583	1.0846	1.2281	1.3380	—	—	—	—	—	—
1.250	0.4546	0.5424	0.6291	0.7391	0.8234	0.9067	1.0354	1.1730	1.3295	1.4496	—	—	—	—	—	—
1.290	0.4696	0.5603	0.6500	0.7639	0.8512	0.9375	1.0709	1.2136	1.3761	1.5009	—	—	—	—	—	—
1.315	0.4789	0.5716	0.6631	0.7794	0.8686	0.9567	1.0931	1.2390	1.4052	1.5329	1.6917	—	—	—	—	—
1.375	0.5014	0.5985	0.6946	0.8166	0.9103	1.0029	1.1464	1.2999	1.4752	1.6099	1.7777	—	—	—	—	—
1.500	0.5481	0.6546	0.7600	0.8941	0.9971	1.0991	1.2573	1.4268	1.6208	1.7703	1.9567	—	—	—	—	—
1.510	0.5519	0.6591	0.7653	0.9003	1.0041	1.1068	1.2661	1.4370	1.6325	1.7831	1.9711	—	—	—	—	—
1.625	0.5949	0.7107	0.8255	0.9716	1.0840	1.1953	1.3682	1.5538	1.7665	1.9306	2.1358	—	—	—	—	—
1.638	0.5998	0.7166	0.8323	0.9796	1.0930	1.2053	1.3797	1.5670	1.7816	1.9473	2.1544	—	—	—	—	—
1.660	0.6080	0.7264	0.8439	0.9933	1.1083	1.2223	1.3992	1.5893	1.8072	1.9755	2.1859	—	—	—	—	—
1.690	0.6192	0.7399	0.8596	1.0119	1.1291	1.2453	1.4258	1.6198	1.8422	2.0140	2.2289	—	—	—	—	—
1.740	0.6379	0.7624	0.8858	1.0429	1.1639	1.2838	1.4702	1.6706	1.9005	2.0781	2.3005	—	—	—	—	—
1.875	0.6884	0.8230	0.9565	1.1266	1.2577	1.3877	1.5900	1.8077	2.0578	2.2513	2.4939	—	—	—	—	—
1.883	0.6914	0.8266	0.9607	1.1315	1.2632	1.3939	1.5971	1.8158	2.0671	2.2616	2.5054	—	—	—	—	—
1.900	0.6978	0.8342	0.9696	1.1421	1.2750	1.4070	1.6122	1.8331	2.0869	2.2834	2.5297	2.7719	—	—	—	—
2.000	0.7352	0.8791	1.0220	1.2041	1.3445	1.4839	1.7009	1.9346	2.2034	2.4117	2.6730	2.9301	—	—	—	—
2.197	—	—	1.1251	1.3262	1.4814	1.6356	1.8757	2.1347	2.4330	2.6644	2.9552	3.2418	—	—	—	—
2.250	—	—	1.1529	1.3591	1.5182	1.6764	1.9227	2.1885	2.4947	2.7324	3.0311	3.3256	3.6776	—	—	—
2.360	—	—	1.2105	1.4273	1.5947	1.7610	2.0203	2.3002	2.6229	2.8735	3.1887	3.4996	3.8717	—	—	—
2.375	—	—	1.2184	1.4366	1.6051	1.7726	2.0336	2.3155	2.6404	2.8927	3.2101	3.5234	3.8981	—	—	—
2.500	—	—	1.2839	1.5141	1.6920	1.8688	2.1445	2.4424	2.7860	3.0531	3.3892	3.7211	4.1186	—	—	—
2.857	—	—	—	—	—	2.1436	2.4613	2.8049	3.2020	3.5110	3.9006	4.2860	4.7483	5.1511	5.7594	—
2.875	—	—	—	—	—	2.1574	2.4773	2.8232	3.2230	3.5341	3.9264	4.3144	4.7800	5.1857	5.7984	6.2440
3.000	—	—	—	—	—	2.2536	2.5882	2.9502	3.3686	3.6945	4.1054	4.5122	5.0005	5.4262	6.0697	6.5380
3.476	—	—	—	—	—	2.6200	3.0105	3.4336	3.9233	4.3051	4.7873	5.2653	5.8401	6.3422	7.1026	7.6575
3.500	—	—	—	—	—	2.6385	3.0318	3.4579	3.9512	4.3359	4.8217	5.3033	5.8824	6.3883	7.1547	7.7139
3.971	—	—	—	—	—	3.0010	3.4497	3.9363	4.5000	4.9401	5.4963	6.0484	6.7132	7.2946	8.1768	8.8216
4.000	—	—	—	—	—	3.0233	3.4754	3.9657	4.5338	4.9773	5.5379	6.0943	6.7644	7.3504	8.2398	8.8898
4.466	—	—	—	—	—	3.3820	3.8889	4.4390	5.0768	5.5750	6.2054	6.8316	7.5863	8.2471	9.2510	9.9857
4.500	—	—	—	—	—	3.4081	3.9191	4.4735	5.1164	5.6187	6.2541	6.8854	7.6463	8.3125	9.3248	10.0657
5.000	—	—	—	—	—	3.7930	4.3627	4.9813	5.6990	6.2601	6.9704	7.6764	8.5282	9.2746	10.4098	11.2416

All tubular products are produced in accordance with ASTM A500.
 In-line galvanized coatings produced in accordance with ASTM 1057.

SQUARES

OD	GAUGE AND NOMINAL WALL THICKNESS															
	20 0.035	19 0.042	18 0.049	17 0.058	16 0.065	15 0.072	14 0.083	13 0.095	12 0.109	11 0.120	10 0.134	9 0.148	8 0.165	7 0.180	6 0.203	5 0.220
0.750	0.3406	0.4047	0.4675	0.5463	0.6060	0.6644	0.7535	—	—	—	—	—	—	—	—	—
0.813	0.3706	0.4407	0.5095	0.5960	0.6617	0.7261	0.8246	—	—	—	—	—	—	—	—	—
0.875	0.4001	0.4762	0.5509	0.6449	0.7166	0.7869	0.8947	—	—	—	—	—	—	—	—	—
1.000	0.4597	0.5476	0.6342	0.7436	0.8271	0.9094	1.0359	1.1701	1.3218	—	—	—	—	—	—	—
1.250	0.5788	0.6905	0.8009	0.9409	1.0483	1.1543	1.3183	1.4934	1.6927	—	—	—	—	—	—	—
1.500	0.6979	0.8334	0.9677	1.1383	1.2695	1.3993	1.6007	1.8166	2.0635	2.2538	—	—	—	—	—	—
1.750	—	—	—	—	1.4906	1.6443	1.8831	2.1398	2.4344	2.6621	2.9472	—	—	—	—	—
2.000	—	—	—	—	1.7118	1.8893	2.1655	2.4631	2.8053	3.0704	3.4031	—	—	—	—	—
2.250	—	—	—	—	—	2.1343	2.4479	2.7863	3.1762	3.4787	3.8590	4.2340	4.6822	5.0711	5.6555	—
2.500	—	—	—	—	—	2.3792	2.7303	3.1095	3.5470	3.8870	4.3150	4.7376	5.2436	5.6835	6.3462	—
3.000	—	—	—	—	—	—	3.2951	3.7560	4.2888	4.7036	5.2268	5.7447	6.3664	6.9084	7.7276	—
4.000	—	—	—	—	—	—	4.4248	5.0490	5.7723	6.3368	7.0506	7.7590	8.6121	9.3582	10.4905	—

RECTANGLES

OD	GAUGE AND NOMINAL WALL THICKNESS															
	20 0.035	19 0.042	18 0.049	17 0.058	16 0.065	15 0.072	14 0.083	13 0.095	12 0.109	11 0.120	10 0.134	9 0.148	8 0.165	7 0.180	6 0.203	5 0.220
0.750 x 1.500	0.5192	0.6191	0.7176	0.8423	0.9377	—	—	—	—	—	—	—	—	—	—	—
0.750 x 2.250	0.6979	0.8334	0.9677	1.1383	1.2695	—	—	—	—	—	—	—	—	—	—	—
1.000 x 2.000	—	—	0.9677	1.1383	1.2695	1.3993	1.6007	1.8166	2.0635	2.2538	—	—	—	—	—	—
1.000 x 3.000	—	—	1.3011	1.5330	1.7118	1.8893	2.1655	2.4631	2.8053	3.0704	—	—	—	—	—	—
1.500 x 2.000	0.8169	0.9763	1.1344	1.3356	1.4906	—	—	—	—	—	—	—	—	—	—	—
1.500 x 2.500	0.9360	1.1192	1.3011	1.5330	1.7118	1.8893	2.1655	2.4631	2.8053	3.0704	—	—	—	—	—	—
1.500 x 3.000	—	—	—	—	1.9330	2.1343	2.4479	2.7863	3.1762	3.4787	—	—	—	—	—	—
1.500 x 3.500	—	—	1.6345	1.9277	2.1541	2.3792	2.7303	3.1095	3.5470	3.8870	4.3150	—	—	—	—	—
1.750 x 2.750	—	—	—	—	1.9330	2.1343	2.4479	2.7863	3.1762	3.4787	—	—	—	—	—	—
2.000 x 3.000	—	—	—	—	2.1541	2.3792	2.7303	3.1095	3.5470	3.8870	4.3150	4.7376	5.2436	—	—	—
2.000 x 4.000	—	—	—	—	—	—	3.2951	3.7560	4.2888	4.7036	5.2268	5.7447	6.3664	6.9084	—	—
2.000 x 6.000	—	—	—	—	—	—	4.4248	5.0490	5.7723	6.3368	7.0506	7.7590	8.6121	9.3582	—	—

OCTAGONS **NEW!**

OD*	GAUGE AND NOMINAL WALL THICKNESS															
	20 0.035	19 0.042	18 0.049	17 0.058	16 0.065	15 0.072	14 0.083	13 0.095	12 0.109	11 0.120	10 0.134	9 0.148	8 0.165	7 0.180	6 0.203	5 0.220
4.783	—	—	—	—	—	—	—	5.0293	5.7533	6.3190	7.0350	7.7466	—	—	—	—

*OD for octagon product is measured across the flats.

All tubular products are produced in accordance with ASTM A500.
 In-line galvanized coatings produced in accordance with ASTM 1057.

WME-011024



4435 South Western Boulevard
 Chicago, IL 60609
 P 800.733.5608
 F 312.275.1596

info@wheatland.com
 wheatland.com
 Follow us on Twitter:
 @WheatlandTube



Wheatland Tube
A ZEKELMAN COMPANY