

ELBOWS WITHOUT THE ELBOW GREASE



Introducing SpeedCouple pre-installed elbow coupling

Available on
rigid steel elbows

Standard &
special radius

Trade sizes 2-6

Listed as
concrete tight

For decades, contractors have had to rely on cumbersome three-piece couplings when installing elbows in tight spaces. Now with SpeedCouple, the process takes half the time. Just turn the coupling, not the elbow, and let the lead-in threads do most of the work. Boost productivity and cut material costs by up to 50% compared to three-piece couplings.

Watch the video at wheatland.com/elbow



Wheatland Tube
A DIVISION OF ZEKELMAN INDUSTRIES



SpeedCouple: Pre-installed Elbow Coupling

Available on
rigid steel elbows
Standard & special radius
Trade sizes 2-6
Listed as concrete tight

SpeedCouple connects in half the time of conventional couplings. Just turn SpeedCouple, not the elbow, and let the lead-in threads do most of the work. It's easier on your crew and your budget!

SPEEDCOUPLE 90° ELBOWS WEIGHTS, DIMENSIONS AND PACKAGING

TRADE SIZE	MIN. RADIUS in.	OFFSET	STRAIGHT	WEIGHT PER ELBOW Each	WEIGHT PER ELBOW WITH COUPLING Each	STANDARD CARTON QTY.
2	9.5	14.54	5.04	6.70	7.58	5
2½	10.5	17.00	6.50	12.00	13.76	Bulk
3	13	19.67	6.67	19.00	20.98	Bulk
3½	15	22.72	7.72	28.00	30.65	Bulk
4	16	23.94	7.94	31.00	34.09	Bulk
5	24	34.90	10.90	68.00	71.97	Bulk
6	30	45.50	15.50	114.00	119.25	Bulk

Note: SpeedCouple elbows shall be listed to safety standards UL-6 and UL-514B. Manufactured in accordance with ANSI® C80.1.
Standard-radius elbows: Available in 90°, 60°, 45°, 30°, 22.5°, 15°, 11.25°
Special-radius elbows: Available in 90°, 60°, 45°, 30°, 22.5°, 15°, 11.25°

Watch the video at wheatland.com/elbow

WEL-052620