

ELBOWS WITHOUT THE ELBOW GREASE



Introducing SpeedCouple pre-installed elbow coupling

Available on
rigid steel elbows

Standard &
special radius

Trade sizes 2-6

Listed as
concrete tight

For decades, contractors have had to rely on cumbersome three-piece couplings when installing elbows in tight spaces. Now with SpeedCouple, the process takes half the time. Just turn the coupling, not the elbow, and let the lead-in threads do most of the work. Boost productivity and cut material costs by up to 50% compared to three-piece couplings.

Watch the video at wheatland.com/elbow



Wheatland Tube
A ZEKELMAN COMPANY



SpeedCouple: Pre-installed Elbow Coupling

Available on
rigid steel elbows
Standard & special radius
Trade sizes 2-6
Listed as concrete tight

SpeedCouple connects in half the time of conventional couplings. Just turn SpeedCouple, not the elbow, and let the lead-in threads do most of the work. It's easier on your crew and your budget!

SPEEDCOUPLE 90° ELBOWS WEIGHTS, DIMENSIONS AND PACKAGING

| TRADE SIZE | MIN. RADIUS in. | OFFSET | STRAIGHT | WEIGHT PER ELBOW Each | WEIGHT PER ELBOW WITH COUPLING Each | STANDARD CARTON QTY. |
|------------|--------------------|--------|----------|--------------------------|---|-------------------------|
| 2 | 9.5 | 14.54 | 5.04 | 6.70 | 7.58 | 5 |
| 2½ | 10.5 | 17.00 | 6.50 | 12.00 | 13.76 | Bulk |
| 3 | 13 | 19.67 | 6.67 | 19.00 | 20.98 | Bulk |
| 3½ | 15 | 22.72 | 7.72 | 28.00 | 30.65 | Bulk |
| 4 | 16 | 23.94 | 7.94 | 31.00 | 34.09 | Bulk |
| 5 | 24 | 34.90 | 10.90 | 68.00 | 71.97 | Bulk |
| 6 | 30 | 45.50 | 15.50 | 114.00 | 119.25 | Bulk |

Note: SpeedCouple elbows shall be listed to safety standards UL-6 and UL-514B. Manufactured in accordance with ANSI® C80.1.
Standard-radius elbows: Available in 90°, 60°, 45°, 30°, 22.5°, 15°, 11.25°
Special-radius elbows: Available in 90°, 60°, 45°, 30°, 22.5°, 15°, 11.25°

Watch the video at wheatland.com/elbow

WEL-122023