



Easy Identification for Tough Environments



Rigid Metal Conduit Now Available in Color!

Applications

Outdoors

*Highly corrosive
environments*

Manufacturing facilities

Energy plants

...and more!

Wheatland Tube's rigid metal conduit comes in eight vivid colors, making it the easiest way to identify critical systems in any tough environment. The vibrant powder-coated finish won't crack, flake or peel during conduit bending. And the UV protective coating prevents fading, even when continuously exposed to direct sunlight. Plus, the hot-dip galvanization protects both the ID and the OD from corrosion. RMC is available in color in trade sizes ½-4.

**Add your customized Call To Action here.
Add your customized Call To Action here.**



Wheatland Tube
A DIVISION OF ZEKELMAN INDUSTRIES

Rigid Metal Conduit Now Available in Color!

Now you can get Wheatland Tube's rigid metal conduit in eight vivid colors. Don't waste time spray-painting or taping when you can get RMC in color. It's made to order, with a quick turnaround.



RIGID METAL CONDUIT WEIGHTS AND DIMENSIONS (10' LENGTHS)

TRADE SIZE	METRIC DESIGNATOR	THREADS/ INCH	WEIGHT PER 100 FT.		NOMINAL OUTSIDE DIAMETER		NOMINAL INSIDE DIAMETER	
			lbs.	kg	in.	mm	in.	mm
½	16	14	82	37.2	0.840	21.34	0.632	16.05
¾	21	14	109	49.4	1.050	26.67	0.836	21.23
1	27	11½	161	73.0	1.315	33.40	1.063	27.00
1¼	35	11½	218	98.9	1.660	42.16	1.394	35.41
1½	41	11½	263	119.3	1.900	48.26	1.624	41.25
2	53	11½	350	158.8	2.375	60.33	2.083	52.91
2½	63	8	559	253.6	2.875	73.03	2.489	63.22
3	78	8	727	329.8	3.500	88.90	3.090	78.49
3½	91	8	880	399.2	4.000	101.60	3.570	90.68
4	103	8	1030	467.2	4.500	114.30	4.050	102.87

Applicable tolerances: Outside diameter ½-1½: ±0.015" (16-41: ±0.38 mm), 2-6 (53-155): ± 1%.

RIGID METAL CONDUIT PACKAGING (10' LENGTHS)

TRADE SIZE	METRIC DESIGNATOR	THREAD PROTECTOR COLOR	QUANTITY/ BUNDLE			QUANTITY/LIFT*			WEIGHT/LIFT		VOLUME/LIFT	
			ft.	m	Pieces	Bundles	ft.	m	lbs.	kg	cu. ft.	cu. m
½	16	Black	100	30.5	—	25	2500	762	2050	929.9	19.4	0.6
¾	21	Red	50	15.2	—	40	2000	610	2180	988.8	26.7	0.8
1	27	Blue	50	15.2	—	25	1250	381	2013	913.1	22.2	0.6
1¼	35	Red	—	—	90	—	900	274	1962	889.9	28.3	0.8
1½	41	Black	—	—	80	—	800	244	2104	954.4	27.2	0.8
2	53	Blue	—	—	60	—	600	183	2100	952.5	36.1	1.0
2½	63	Black	—	—	37	—	370	113	2068	938.0	35.0	1.0
3	78	Blue	—	—	30	—	300	91	2181	989.3	41.5	1.2
3½	91	Black	—	—	25	—	250	76	2200	997.9	43.3	1.2
4	103	Blue	—	—	20	—	200	61	2060	934.4	48.6	1.4

* The quantity per lift conforms to the National Electrical Manufacturers Association Standards Publication RN-2, Packaging of Master Bundles for Steel Rigid Metal Conduit, Intermediate Metal Conduit (IMC) and Electrical Metallic Tubing (EMT). Pack quantities for Canadian distribution do not comply with NEMA RN-2.

SPECIFICATIONS FOR POWDER COATING

PENCIL HARDNESS	ASTM D3363 H-4H
WEATHERING	1,000+ hours
GLOSS	ASTM D523 60% 30-99
ADHESION	ASTM 3359-5B 100%

AVAILABLE IN 8 COLORS



Wheatland Tube
A DIVISION OF ZEKELMAN INDUSTRIES